

# PELVI.LOC® PL-GF Genuframe

PELVI.LOC® Lower Leg Belts

HMV.Nr.: 18.99.99.0905



## Version

The two-dimensionally shaped pads are set in front via the perforated belt. Timing belts **R24-BL-RNI-305** and buckle **B24-AE-BL** provide high load capacity, also available with other buckles and toothed belts.

The lower leg strap is individually adjusted to the sitting position by means of the ratchet buckle and can be adjusted to the nearest millimeter. Likewise, the strap can also be opened quickly via the ratchet buckle.

## Amendment

With other buckles B24-star, B19-GO available.

Clamping clips for wheelchair frame.

## Article numbers

**RS-20** Tube diameter 20 mm

**RS-22** Tube diameter 22 mm

**RS-25** Tube diameter 25 mm

**RS-30** Tube diameter 30 mm

**RS-32** Tube diameter 32 mm



## Scope of application

Pelvi.Loc - lower leg - belt prevents forward sliding of the pelvis in a wheelchair.

## Special Features

Also with other buckles, e.g. (B24 Star, B19-GO) available.

## Article numbers

**PL-UG-XXS** for SW 12-20 cm

**PL-UG-XS** for SW 16-24 cm

**PL-UG-S** for SW 20-32 cm



**PL-UG-M** for SW 30-40 cm

**PL-UG-L** for SW 36-46 cm

**PL-UG-XL** for SW 44-52 cm

## Technical Data

	XXXX Bambino	XXS	XS	S	M	L	XL
Seat width (cm)		12 - 20	16 - 24	20 - 32	30 - 40	36 - 46	44 - 52
Padding size (cm)		12 x 7	18 x 7	21 x 8	25,5 x 8	26,5 x 8,5	28,5 x 9
Weight (g)		200	220	220	280	280	300
Predetermined breaking point (at approx. kg)		60	60	60	80	80	80

Ratchet size XXXS - XXS	1,9 x 0,2 x 40,0 cm	<p>Product is latex-free</p> 	
Ratchet size XS - S	1,9 x 0,2 x 40,0 cm		
Ratchet size M - L - XL	2,4 x 0,2 x 40,0 cm		
Buckle size XXXS			
Buckle size XXS	B-19-ERGO-BL		
Buckle size XS - S	B-19-ERGO-BL		
Buckle size M - L - XL	B-24-ERGO-BL		
Hole-strap			